



BSC09

Product Description:

Product Introduction

BSC09 is a widely used Access Control in the office. Choosing a lot of stable original parts, strictly follow the national security product standard .BSC09 is suitable for the entrances and exits of office, factory, hotel, school, etc. All input /output are using anti-jamming protection and over-voltage/circuit protection. The product experiences the strict degradation test before leaving factory. The greatest advantage of BSC09 is easy to install, with multifunctional & elegant design and reasonable price .

Benefits :

- One fingerprint develop the whole world
- Adopt high reliable industrial component parts and optical sensor, watchdog monitor to avoid unit hang ,unique reset key keeps the unit well work
- Easy to install all the cable connection EM lock installation are the same to the traditional IC/ID Access control
- One-way alarm output: dismantlement alarm, threatens alarm, unlock illegally alarm, not block alarm

Technical Specifications

- Hardware platform : Bio510
- Operating system : Linux
- User capacity: 3000
- Transaction capacity: 100000
- Sensor: Biosecurity Sensor
- Algorithm version : 9.0 &10.0 algorithm
- Access Control: 50 Time Zone, 5 Grouping, 10 Combination, Holiday Management, support many fingerprints

access, support standalone work

- Communicational: TCP/IP or RS232 and RS485, USB host
- Keyboard and Display: LCD with 80 character and figure keypad
- Power: 12 V DC 3A
- Identification speed: ≤ 2 seconds
- FRR: $\leq 1\%$
- FAR: $\leq 0.0001\%$
- Temperature operating: $0^{\circ}\text{C} - 45^{\circ}\text{C}$
- Humidity operating: 20%-80%
- Language: simplified Chinese, traditional Chinese, English, other Languages
- Standard: Wire Doorbell, Wiegand OUT, Wiegand IN
- Optional: ID/HID/Mifare card, Webserver, Short message, Workcode, RIS, Antipass-back
- Optional: Webserver, Workcode, RIS, Multi-identification, 9 Digits User ID, Schedule Status

Dimension: 212.3*95.8*53.5mm