



# 1042TW-N

Industrial surface mount magnetic contact

## Industrial Surface Mount Contact

The Sentrol 1045T series features a wider make distance, which permits faster installation, accommodates greater misalignment and works better on steel without time-consuming brackets. A wider break distance helps prevent false alarms caused by loose fitting doors. Sentrol-specified contacts keep the 1045 series from sticking or freezing on seldom-used doors.

## Applications

The contacts are used to protect openings such as metal entry/exit doors, overhead doors, roof hatches or hinged skylights.

## Durability and dependability

The Sentrol high performance magnetic contacts have been designed to facilitate installation and ensure durability and dependability. Most are conservatively rated at 10,000,000 cycles, guaranteeing a long life. Every reed connection is hand soldered and each magnetic contact is tested before they leave the factory, 100% of the time.



## Standard Features

- Designed for commercial and industrial applications
- Can be used on steel without brackets
- Rugged construction
- Mounting screws
- Concealed terminals resist tampering and inadvertent shorting

# 1042TW-N

Industrial surface mount magnetic contact

## Specifications

Gap distance (max)	76 mm
Connections	Screw terminals
Contact	NC
Supervised loop	No
Dimensions (L x W x H)	99 x 15 x 18 mm
Color	White
Remarks	

## Ordering Information

Part No.	Description
1042TW-N	Industrial surface mount magnetic contact

