DHI-ART-ARC2000B-06-C35

Alarm Security Kit

Features

• WiFi for communication
• 28 wireless detectors+8 wireless keyfobs+4 wireless sirens, transimission range up to 150m open space
• Airfly technology, 2-way dynamic 128-bit AES encryption.
• Globally control. Know what's happing 24/7, preview and playback video, receive notifications via DMSS anywhere anytime
• Easy installation, no wiring. No contracts and monthly fees
• 1 Alarm Hub(WiFi), 2 PIR detector, 2 Door/Window detector, 2 Remote control, 1 IPC-C35

Detection Range	12m×12m, 90°
Alarm prompt	Red LED, can be set to switch off
Sensitivity	Two level (jumper)
Wireless Frequency	433/868MHz
Transmit power	10dBm
Transmit distance	150m open area/no interference
Pet immunity	≤18Kg
Resistance light	6500LUX
Working environment	-10°C~+50°C, humidity <95°
Overall dimensions/weight	105mmx62mmx41.3mm/0.1kg
Tamper	Unit protection and leaving-wall protection
Power	1xCR123A battery
Installation height	Wall mount, 2.2-2.5m

Technical Specification

ARC2000B-W

Name	Wireless alarm hub
Wireless Capability	28 wireless detectors,8 wireless keyfobs, 4 wireless sirens, 2-way communication
WiFi Frequency	2.4GHz(IEEE802.11b/g/n)
Wireless Frequency	433/868MHz
WiFi Transmitting Power	≤18dBm
Wireless Transmitting Power	≤10dBm
Wireless Transmitting Distance	150m(open space, no interference)
Supply Voltage	DC5V
Power Consumption	≤5W
Working Temperature	-10℃~55℃
Installation	Desktop and wall-mounted
Dimension	140mm*142mm*19.5mm
Weight	0.2kg

ARD1231-W

Name	Wireless passive infrared sensor
Detection	Passive infrared

ARD311-W

Name	Wireless door sensor
Motion distance	25-40mm
Alarm prompt	Notification LED light, can be set to switch off
Wireless Frequency	433/868MHz
Transmit Power	10dBm

DHI-ART-ARC2000B-06-C35

Transmit Distance	150m(open area/no interference)
Tamper	Front cover and rear cover protection
Power	1xCR123A battery
Installation Way	Screw and glue
Dimensions	84*39*22mm
Weight	0.1kg
Temperature	-10°C~50°C
Humidity	< 95%
Installation	Screw or glue to mount

ARA22-W

Name	Remote control
Working Voltage	DC3.0V
Frequency	433/868MHz
Transmit Power	10dBm
Key	Away Arm/Stay Arm/Disarm/SOS
Temperature	-10°C~55°C
Ingress protection	IP20
Dimension	62*30*14mm

Ordering Information

DHI-ART-ARC2000B-06-C35	Alarm Security Kit, 433MHz
DHI-ART-ARC2000B-06-C35P(868)	Alarm Security Kit, 868MHz