

4 CHANNEL REAL TIME STANDLONE DVR

MODEL: QH-D2104A-A



Specifications

Operation System	:	Linux
Video	Video System	: NTSC/PAL Switch Selectable
	Input	: BCN*4, 1.0V p-p 75 ohm
	CVBS	: 1CH, BNC
	VGA out put	: STANDARS VGA*1: 1280 x 1024
Audio	Input	: 4CH, RCA
	Output	: 1CH, RCA
	Talkback	: YES
Control	Mouse	: 2*USB 2.0
	IR Controller	: YES
Storage	Build in interface	: SATA 2.6*2 (2*HDD 2TB)
Display	Division	: 1, 4
	Zoom	: Preview and Playback Zoom Support
	Compression	: H.264 MAIN PROFILE
	Recording Mode	: Manual/ Schedule/ Motion Detection/ Sensor
	Resolution	: NTSC: 704*480, 704*240, 352*240 PAL: 704*576, 704*288, 352*288
Recording	Record Frame Rate	: NTSC: 120FPS@D1 PAL:100 FPS@D1
	Quality	: Worst, Worse, General, Good, Better, Best.
	Motion Detection	: Sensitivity: Multi Level, 8*8 Grid
	Water Mark	: YES
Playback	Playback Frame Rate (PAL)	: 120(100)FPS@CIF
	Multi Channel Playback	: 1/4
	Speed	: Normal,SLOW&FF(1/4,1/3,1/2,1*,2*,3*,4*)
	Search Method	: Time, Even, Channels and Calendar
Communication	Remote Software	: Remote Client, IE Brower, Mobile, CMS, Firefox, Chrome, Safari
	Remote Operation	: Remote view, remote playback, remote setup
	Network Service	: TCP/IP, UDP, HTTP, DDNS, SMTP(SSL), LAN, DHCP, PPPOE
Backup	GUI Interface	: Supported GUI 16 Bit True Color
	PTZ Protocol	: 1*RS485, Support 18 Kinds of Protocol
	External	: 2*USB2.0, Removable DVD-RW, USB Disk up to 32G
	Network	: YES
	File	: H.264 Compression / AVI
General	Alarm In/Out	: 4 CH / 1CH
	RS-485	: 1
	Unit Dimension(mm)	: W340xD268xH64mm
	Operation Temperature	: 10°~40°
	Working Humidity	: 10% ~ 90%
Power Consumption	: DC 12V,4A,10~15W (Exclude HDD)	