



SBTL6200 Series

SBTL6200 Single lane speed gates

SBTL6211 Single lane speed gates

(w/ controller and RFID reader)

SBTL6222 Single lane speed gates

(w/ controller and fingerprint RFID reader)

SBTL6233 Single lane speed gates

(w/ visible light facial recognition devices)

SBTL6200 is designed to work with SBTL6000 series for forming multiple lanes.

Description

The SBTL6200 is a single lane Swing barrier turnstile series designed for Stable operation, free of noise and environmental protection energy saving. The unit adopts international stainless steel which makes SBTL6200 highly durable.

The barriers of SBTL6200 are normally keeping in a locked position in this circumstance it refuse the access to the secured side. Upon SBTL6200's reader(RFID, fingerprint and facial) positively recognizing a users valid access card, fingerprint and face, the barriers swing automatically, thus allowing users passage to the secured side.

The Personalized LED indicator design can guide people directly.

Features

Reliability

- SUS304 stainless steel case ensures long-lasting durability.
- High quality electrical components safety features.
- Ergonomic design makes card, finger int and face, authentication fast simple for users.

Built-in Reader Integration

- SBTL6200 series already integrated with customers preference for either card, fingerprint or face, access control reader which greatly reduces installation time & expenses.
- SBTL6200 series and associated access control readers have passed the factory test before shipment.

Simplification

- Simplify structure and connection, easy to maintain.
- Control board with LCD screen, easy to operate.
- Special modular design for the panel to support a faster switch between reader and turnstile. Reader installation can be finished by simple pull-out and pull-in.

Specifications

power requirement	AC 100~120V/200~240V, 50/60Hz
Working temperature	-28°C~ 60°C
Working humidity	5%~80%
Working environment	Indoor/Outdoor(if sheltered)
Lan width(mm)	600
Footprint(mm*mm)	1400*763
Dimension(mm)	L=1400, W=180, H=1000
Dimension with packing(mm)	L=1484, W=394, H=1104
Net Weight(kg)	81
Weight with packing(kg)	116
LED indicator	Y
Cabinet material	SUS304 Stainless Steel
Lid material	Acrylic
Barrier material	Acrylic
Barrier movement	Retracting
Emergency mode	Y
Security Level	Medium
MCBF	2 million

Dimensions (mm)

