



NVR 16 CANALES, 8 PUERTOS POE, 2 BAH

MODEL: SNR21-1608P



Main Features:

- Connectable to the third-party network cameras like like ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, PSIA, SAMSUNG, SANYO, SONY, Vivotek and ZAVIO.
- Up to 16 network cameras can be connected.
- Support live view, storage, and playback of the connected camera with up to the resolution of 5 megapixels.
- Simultaneous HDMI and VGA outputs at up to 1920×1080 resolution.
- New GUI and support starting record with one key;
- Holiday recording;
- Realize instant playback for assigned channel during multi-channel display mode.
- Up to 16-ch synchronous playback at 4CIF resolution.
- Customization of tags, searching, and playing back by tags.
- Locking and unlocking record files.
- Support HDD quota mode; different capacity can be assigned to different channel.
- 2 SATA hard disks can be connected.
- 1 self-adaptive 10M/100M/1000M network interface is provided;
- Support Safecom DDNS (Dynamic Domain Name System);
- Support network detection, including network delay, packet loss, etc.

Specifications

Video/Audio input	IP video input	8-ch	16-ch	32-ch
	Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)		
Network	Incoming bandwidth	50Mbps	100Mbps	200Mbps
	Outgoing bandwidth	80Mbps		
	Remote connection	128		
Video/Audio output	Recording resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
	Frame rate	Main stream: 50 fps (P) / 60 fps (N) Sub-stream: 50 fps (P) / 60 fps (N)		
	HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz		
	Audio output	1-ch, RCA (Linear, 1kΩ)		
Decoding	Live view / Playback resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF		
	Capability	8-ch@720P, 6-ch@1080P	16-ch@4CIF 12-ch@720P 6-ch@1080P	16-ch@4CIF 12-ch@720P 6-ch@1080P
Hard disk	SATA	2 SATA interface for 2 HDDs		
	Capacity	Up to 4TB for each disk		
External interface	Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface		
	USB interface	1 × USB 2.0 and 1 × USB 3.0		
	Alarm in/out (Optional)	4 / 1		
Others	Power supply	12V DC		
	Consumption (without hard disk)	≤ 10W		
	Working temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)		
	Working humidity	10 % ~ 90 %		
	Chassis	380 chassis		
	Dimensions (W × D × H)	380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)		
	Weight (without hard disk)	≤ 1 kg (2.2 lb)		

* Specifications are subject to change without prior notice.