



Feature

- All channel 720P@25/30FPS realtime recording, 1/4CH playback simultaneously
- Compatible with Analog 960H/D1
- Support 10M/100Mbit/s network interface
- Free ISS Management software
- Mobile surveillance supported, Including iPhone, iPad, Android
- Support browser IE 6.0 Above;
- Free DDNS server: HDCCTVDDNS
- P2P support
- 1080P HD Diaplay
- 2 SATA, Max 4TB per HDD

Model NO.	SVG11-1601
OPERATION SYSTEM	LINUX
VIDEO	
VIDEO SYSTEM	NTSC/PAL Switch Selectable
INPUT	BNC*16,1.0Vp-p,75ohm
SPOT	NA
HDMI OUTPUT	1 HDMI Output
VGA OUTPUT	1 VGA Output
AUDIO	
INPUT	2CH, RCA
OUTPUT	1CH, RCA
TALK BACK	YES
CONTROL	
MOUSE	2*USB
KEYBOARD	NA
STORAGE	
BUILD IN INTERFACE	SATA 2.6 *2
DISPLAY	
DIVISION	1, 4, 9, 16
ZOOM	Preview&Playback Zoom Support
RECORDING	
COMPRESSION	H.264(High profile)
RECORDING MODE	Manual/Schedule/Motion Detection/Sensor (Optional)
RESOLUTION	Mode 1: 16CH 720P

	Mode 2: 8CH 720P + 8CH 960H
	Mode 3: 16CH 960H
RECORD FRAME RATE	PAL: 16CH 720P@25fps, NTSC: 16CH 720P@30fps
QUALITY	Worst, Worse, Bad, Normal, Better, Best
PLAYBACK	
SYNC PLAYBACK	1, 4
SPEED	Normal, FF(1X, 2X, 4X, 8X,), Slow (1/2X, 1/4X, 1/8X)
SEARCH METHOD	Time, Event, Channels and Calendar
COMMUNICATION	
REMOTE ACCESS	IE (6.0 and above), ISS (Windows XP/WIN7/WIN8), ISS MOBILE2 (IOS, Android)
REMOTE OPERATION	Remote view, remote playback, remote setup
NETWORK SERVICE	TCP/IP、PPPOE 、 DDNS、 FTP、 NTP UPNP
MOBILE DEVICE	Iphone, Ipad, Android
3G EXTERNAL MODULE	Yes, with USB 2.0 Port
WAN RJ45	Yes
WIFI EXTERNAL MODULE	Yes, with USB Port
GUI INTERFACE	Supported GUI 16 Bit True Color
PTZ PROTOCOL	PELCO-D, PELCO-P, etc 17 kinds of protocol
BACKUP	
INTERNAL	NA
EXTERNAL	2*USB
NETWORK	YES
FILE FORMAT	AVI/dav
GENERAL	
ALARM IN/OUT	NA
RS-485	1
RS-232	NA
UNIT DIMENSION(mm)	440mm×285mm×45mm
OPERATION TEMPERATURE	10°~40°
WORKING HUMIDITY	10% ~ 90%
POWER CONSUMPTION	DC 12V,3A, <15W (Exclude HDD)