



IP DOME CAMERA
IR 2MP 2.8-12MM POE
MODEL: SVN11-204R



Highlights

- H.264, M-JPEG, JPEG video encoding compression
- Support 30FPS@720P/960P/1080P resolution real-time encoding
- Support CGI/SDK/GB28181 Development, ONVIF V2.4, ONVIF ProfileS (Platform/NVR: Milestone QNAP,AXXON, HIKVISION, DAHUA, DIGIFORT, EXACPVISION, VIDEONET, NUUO, VIDEOINSIGHT, GEOVISION. ONSSI. SYNOLOGY)
- IE BROWSER/SAFARI/GOOGLE CHROME/FIREFOX/OPERA, Search Tool, ISS PC, ISS Mobile Phone/PAD, IPHONE, IPAD), ISS PRO
- Support dual-encoding streams: Main stream, sub stream
- Support bi-directional real time audio transmission
- Support multi-viewer to access concurrently
- Support privacy protection mode, motion detection and sensor alarm functions
- Auto-retrieve function and auto-connection network
- Network Protocol: TCP/IP, UDP, HTTP, HTTPS, 802.1x, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, FTP, UPNP
- FREE DDNS: HDCCTVDDNS, NO-IP, DYNDNS, 3322
- Advance Feature: HTTPS, 802.1X, AES, ROI Encoding, Multicast, DWDR, 3D-DNR, Secure Login, RTSP, Authority, Video Watermark, Quick Setup, Digital Zoom, Auto Maintain

Camera	
Day/Night	ICR
Min. Illumination	0.01lux @F1.2,AGC on,0 lux with IR on
Lens	2.8-12mm VF Lens
IR LED	18Leds

* Specifications are subject to change without prior notice.



IR Distance	3-20m
Electronic Shutter	1/20~1/30000s
Video	
Compression	H.264/M-JPEG
Max.image Resolution	1920x1080
Frame Rate	30fps @ 1080P
Bit Rate	Main Stream: 1000~12000kps Sub Stream: 512~2048kbps
Audio	
Compression	G.711
Talkback	YES
Network	
Protocol	TCP/IP, UDP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SM NTP, SNMP, FTP, UPNP, NTP
Compliance	ONVIF V2.4(1.02 backward compatible) CGI
PC Client and Browser	ISS, IE6.0 and above, Google Chrome, Mozilla Firefox, Mac Safari
Mobile phone	iPhone, iPad, Android
WIFI	NA
WIFI Encryption	NA
3G Network	NA
Interface	
Video Output	NA
Audio Input	1 CH 3.5mm audio interface, MIC IN/LINE IN
Audio Output	1 CH 3.5mm audio interface
Alarm Input	NA
Alarm Output	NA
LAN	1 RJ45 10M / 100M ethernet port
RS-485	/
Storage Interface	Built-in micro sd slot, up to 64GB
PIR	NA
Reset Button	NA
General	
Working Temperature	-10° ~ +50°
Working Humidity	0% - 90%

* Specifications are subject to change without prior notice.

Protection Level	Vanproof and IP66
Power Supply	12 VDC \pm 10% PoE(802.3af)
Consumption	4.4W IR ON 2.8W IR OFF
Dimension	154*154*116mm
Weight	1000g