

## VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact



### Standard Features

---

- Detects all known types of attack
- Advanced signal processing differentiates between ambient noise and real attacks
- Protects any solid structure
- Remote test capability
- Adjustable sensitivity
- Advanced tamper protection
- Complete line of accessories
- Easy to install

# VVS302-PLUS

Seismic detector for ATM's and night deposit boxes, NC contact

## Specifications

General	
Low voltage alarm	7.5 V
Tamper protection	Temperature 84 °C, drill shield, opening contact, pry-off contact
Alarm indication	LED-indication screw no. 3
Application Type	ATM, Night Safe Deposit Boxes
Detection	
Range	3 to 14 m radius
Sensitivity adjustment	5 steps of approx. 6 dB each
Inputs/outputs	
Test output	Yes
Electrical	
Power supply value	9 to 15 VDC
Current consumption	8.6 mA
Physical	
Physical dimensions	81 x 101 x 28 mm
Net weight	380 g
Environmental	
Operating temperature	-20 to +55 °C
Relative humidity	90%
IP-rating	IP30
Operating voltage	9 - 15 Vdc, 2 V max ripple ptp
Current draw	Nominal 8.6 mA
Alarm contact	NC
Alarm indication	LED output (terminal 3)
Sensitivity adjustment	5 steps of approx. 6 dB each
Test output	Analog output (terminal 4)
Range	3 - 14 m radius - depending on attack tool
Tamper protection	
Temperature	84 °C
Drill shield	Yes
Tamper contact	Yes
Pry-off tamper	Yes
Low voltage alarm	7.5 Vdc
IP rating	IP30
Operating temperature	-20 °C till +55 °C
Relative humidity	90% at 30 °C
Dimensions (L x W x H)	81 x 101 x 28 mm
Color	Grey, RAL 7035
Weight	380 g

## Ordering Information

Part No.	Description
VVS300-PLUS	Seismic detector for safes and vaults, NC contact
VVS320-PLUS	Seismic detector for safes and vaults, SPDT contact
VVS302-PLUS	Seismic detector for ATM's and night deposit boxes, NC contact
VVS322-PLUS	Seismic detector for ATM's and night deposit boxes, SPDT