



## ID Thin proximity card

### Product Description

The RFID proximity access card offers 125KHz ISO Format proximity technology and customization of printing images on both sides. It is used for applications such as access control system, time and attendance system, visitor management and so on. Gloss or Matte surface and optionally can include the number printed on it.



### Features

- ✓ Only read.
- ✓ Optionally Read and Write (Temic T5577 technology)
- ✓ Compatibility with all ZKSoftware proximity ID readers.
- ✓ Optionally provides an external number printed for easy identification and control.
- ✓ Custom pre-printed artwork available.
- ✓ Support formats up to 26 bits Wiegand format.
- ✓ Meets ISO standard for thickness.
- ✓ Compatible with EM4100 chip data format.

### Specifications

<u>Chip</u>	TK4100
<u>Working Frequency</u>	125KHz
<u>Maximum Read Range</u>	2-15cm
<u>Dimensions</u>	54W x 86L x 0,76H mm
<u>Card Construction</u>	Thin, Flexible polyvinyl chloride (PVC) laminate
<u>Operating temperature</u>	-45°C to 70°
<u>Weight</u>	9 gram
<u>ISO Format</u>	125KHz.
<u>Options</u>	<ul style="list-style-type: none"><li>• External card numbering.</li><li>• Gloss or Matte surface</li><li>• Custom artwork (text or graphics)</li></ul>