

CAMARA IP BULLET C/IR HD LENTE 6MM MODEL: ZKIP372-POE



Specifications

Camera

Image Sensor	: 1/3" megapixel WDR progressive CMOS
Camera Lens Type	: 6mm fixed aperture lens
Image Resolution	: 1280*720
Minimum Illumination	: 0.1Lux (IR off), 0 Lux (IR on)
IR Distance	: 60° projection angle, 15~20 meters valid
Day/Night Mode	: ICR-cut filter switch
Video Coding	
Main Processor	: Hi3512
Operation System	: Built-in Linux
Video Compression	: H.264 main profile level 3
Audio Compression	: G.726/G.711
Video Resolution	: Main stream: 1280*720 : Secondary stream: 320*240
Video Frame Rate	: 1~25 frame optional
Video Parameter	: Brightness, contrast, saturation, color adjustable
Function Interface	
Audio Input	: 1 channel line/Mic input
Audio Output	: 1 channel line output
Alarm Input	: 1 channel on/off alarm input (NO/NC settable)
Alarm Output	: 1 channel on/off output, external max working voltage 120V AC 1A/24V DC 1A
Motion Detection	: 4 independent detection areas settable
Control Interface	: 1 RS-485 interface
Storage	: Support local TF card to store video and snap, up to 32G
Network Interface	: 10Base-T/100Base-TX Ethernet interface : WIFI 802.11b/g/n wireless network (optional)
Protocol	: TCP/IP, HTTP, TCP, UDP, ARP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP
Work Environment	
Power Supply	: 12V DC 1.5A : PoE: 802.3af PoE standard (optional)
Power Consumption	: 13W max
Working Temperature	: -10°C ~ 55°C, 10~95 RH
Protection Rating	: IP66
Weight	: N.W.: 1.80 KGS G.W.: 2.60 KGS