

CAMARA IP MINI DOMO HD LENTE 6MM WDR MODEL: ZKMD470-POE



Specifications

Camera

Sensor	: 1/3" megapixel WDR progressive CMOS
Resolution	: 1280x720
Lens	: 6mm fixed lens
Minimum illumination	: 0.1 Lux
Day/Nigh	: N/A
Video Coding	
Main processor	: HI3512
Operation system	: built-in Linux
Video compression	: H.264 main profile level 3
Audio compression	: G.726/G.711
Compression rate	: Main stream: 1024Kbits/S~6114Kbits/S settable : Secondary stream: 32Kbits/s~512Kbits/s settable
resolution	: Main stream: 1280x720 : Secondary stream: 320x240
Frame rate	: NTSC: 1-30 frames, PAL: 1-25 frames optional
Video parameter	: Brightness, contrast, saturation adjustable
Function Interface	
Audio input	: Built-in Microphone
Audio output	: N/A
Alarm input	: N/A
Alarm output	: N/A
Motion detection	: 4 independent areas
Control interface	: N/A
Storage	: Supports local TF card to store video clips and snapshots, up to 32G
Network interface	: 10Base-T/100Base-TX Ethernet; : WIFI 802.11b/g/n wireless network (optional)
Protocol	: TCP/IP, HTTP, TCP, UDP, ARP, SMTP, FTP, DHCP, DNS, DDNS, NTP, UPNP, RTSP, Onvif
Work Environment	
Power supply	: 12V DC 1.5A : PoE: 802.3af PoE standard (optional)
Power consumption	: 8W max
Work temperature	: -10°C ~ 55°C
Work humidity	: 10 ~ 95%RH