

| Table 1: UL Listed Models and Ranges |                            |                                      |                                       |        |                         |        |          |  |
|--------------------------------------|----------------------------|--------------------------------------|---------------------------------------|--------|-------------------------|--------|----------|--|
| Model                                | Regulated<br>UL<br>Voltage | Average<br>RMS<br>Current*<br>(AMPS) | Reverberant dBA<br>Per UL 464 @ 10 ft |        | Anechoic dBA<br>@ 10 ft |        | Mounting |  |
|                                      |                            |                                      | Continuous                            | Code 3 | Continuous              | Code 3 | Options  |  |
|                                      |                            |                                      | dBA                                   | dBA    | dBA                     | dBA    |          |  |
| MIZ-24S                              | 24 VDC                     | 0.025                                | 83.2                                  | 78.8   | 87.9                    | 87.9   | В        |  |
|                                      | UL max*                    | 0.026                                | 85.8                                  | 81.3   | 90.6                    | 89.7   | В        |  |

## Ordering Information

| Model Number | Part Number | Description                                 |  |
|--------------|-------------|---|--|
| MIZ-24S-R    | MIZ-24S-R   | 24V Selectable temporal / continuous. Red   |  |
| MIZ-24S-W    | MIZ-24S-W   | 24V Selectable temporal / continuous. White |  |