

# NEW! CPX200N CONTROL PANEL

FUNCTIONAL / SIMPLE / CUSTOMISED BY YOU



COMING SOON  
APPLICATION FOR  
SMARTPHONE



NOW ALSO IN WIRELESS VERSION

## CALYPSO

WIRELESS  
CONTROL PANEL  
INTEGRATED WITH  
GSM/GPRS  
COMMUNICATOR



CREATING A SENSE OF SECURITY  
SINCE 1989

# THE CPX200N CONTROL PANEL

is a device that meets the basic requirements for the protection of a small and medium-sized objects. Simple functionality, service and fast installation are the main advantages of our control panel. Small dimensions and modern design of keypad, 7 zones possible to grouping into two partitions make CPX200N one of the best solution on the market.

For more demanding , we created a **CALYPSO** system that reliably meets the requirements of more complex objects. Both panels support up to 3 keypads, so the alarm can be armed / disarmed from 3 different places. **It is important especially in offices, service points where there are backdoors or in single-family houses with balcony doors, garages.**

With the use of wireless, dedicated detectors, you don't need to distribute meters of cables. You can in easy way put the detector anywhere. **CALYPSO** system can be operated via nine 4-button remote controls, which functionality can be freely configured. Arm / disarm the system by radio is confirmed each time by buzzer.

**CALYPSO** supports up to 16 lines, including 9 wireless. In each of our panel is the ability to divide the inputs into 2 zones. User can assign any number of lines to each zone. There will be available soon the application on the mobile phone.

Currently our control panels make it possible to program the SMS messages of up to 10 different users.

## IN SHORT:

	CPX200N	CALYPSO
<b>Transmission</b>	GPRS	GPRS
<b>SMS to monitoring station</b>	YES	YES
<b>Wired zones</b>	7	7
<b>Wireless zones</b>	-	9
<b>Partitions</b>	2	2
<b>Supported keypads</b>	3	3
<b>Key fob</b>	-	YES, max 9 pcs
<b>Remote control</b>	YES, with SMS, GPRS	YES, with SMS, GPRS or using application for smartphone

Control panels produced by EBS meets the requirements of **EN 50131, Grade 2.**





## Our systems give you **warranty** of

- reliable data transmission (GPRS communicator integration), AES encryption
- quick and easy configuration
- customised solution



## Application

- small and medium-sized objects, such as offices, commercial premises, houses, small industrial buildings, garages and holiday houses

Guarantee of quality and functionality in a small and medium-sized objects, where you need fast installation without unnecessary wiring.

# CALYPSO SYSTEM INCLUDES:

Wireless sensors integrated with **CALYPSO** system:

The **MC-10** wireless magnetic contact allows detection of opening doors/windows.

- Low power consumption
- Supervisory signal every 15 minut
- Tamper signal if open cover
- Battery status control (low-power signal)
- Max transmission distance: 300 m (open space)
- Size: detector 85x26x32 mm / magnet 64x13x13 mm

The **PIR-10** wireless motion detector allow a motion detection in restricted areas.

- Lithium battery 3V: life cycle 12 months in normal working conditions.
- Dual passive infrared detection technology.
- Temperature compensation.
- Improved immunity to false alarms.
- Improved resistance to white light interference (optical Fresnel lens).
- Improved resistance to fluorescence interference.
- Supervisory signal every 15 min.
- Low power consumption.
- Battery status control (low-power signal)
- Max transmission distance: 300 m (open space)
- Size: 105x58x38 mm

**RC-10** Remote control with four programmable buttons.



# TECHNICAL PARAMETERS

CPX200N (wired) & CALYPSO (wireless) parameters	
Transmission channels	GPRS, SMS
Wired zones	7
Wired zones type	NO / NC / EOL-NO / EOL-NC / DEOL-NO / DEOL-NC
Response types of zones	<ul style="list-style-type: none"> <li>- instant</li> <li>- delay</li> <li>- 24h burglary</li> <li>- arming / disarming</li> <li>- 24h tamper</li> <li>- interior delay</li> <li>- 24h burglary silent</li> </ul>
Partitions	2
Outputs	<b>1 monitored</b> alarm output, OC type, high-current (max. current 1.1A) <b>2 monitored</b> alarm outputs, OC type, low-current (max. current 50mA)
Output functions (ways of control)	<ul style="list-style-type: none"> <li>- alarm</li> <li>- standby indicator</li> <li>- power supply fault</li> <li>- communication loss</li> <li>- GSM jamming indicator</li> </ul>
Power output +12V	<b>1 signalling</b> device output (max. current 350mA) <b>1 detectors</b> output (max. current 350mA) <b>1 keypad</b> output (max. current 100mA)
Keypads	max. 3
Users (admin / installer / user)	1 / 1 / 8 (possible remote administration of users)
Users SMS	YES, 10 different phone numbers
Events bufer	min. 500
Quantity of system / technical events stored in history	min. 2000
Timestamp event	YES
GPRS/SMS transmission security	AES encryption
Status LEDs (functions)	3 LEDs (GSM signal level, device state and faults)
Buttons (functions)	2 buttons (startup without mains power supply, restore default codes)
Configuration	<b>Remote:</b> GPRS, SMS, CSD <b>Local:</b> PC through RS232 (required cable: GD-PROG)
Remote firmware update	YES
GSM module	u-blox LEON-G100 (GSM 850/900/1800/1900 MHz)

Power supply parameters - PCB (without casing)	Voltage supply	18V <sub>AC</sub> (acceptable: 16-20V <sub>AC</sub> )
	Required transformer power	min. 20VA
	Power consumption (average / max)	120mA/1100mA@18V <sub>AC</sub> (average mesured: fully charged battery, established connection with server, connected keypad, no sensors connected)
Power supply parameters - PCB in casing	Average current consumption; lack of external supply (without keypad / with keypad / with 3 keypads)	60mA/85mA/135mA (fully charged battery, no sensors connected, established connection with server)
	Voltage supply	230V <sub>AC</sub> (acceptable: 190-250V <sub>AC</sub> )
Charging module functions	Power consumption (average / max)	3W/20W@230V <sub>AC</sub>
		<ul style="list-style-type: none"> <li>- protection against reverse battery connection</li> <li>- AC failure signalization</li> <li>- low battery/no battery signalization</li> <li>- protection against short circuit battery output</li> <li>- polymer fuse</li> </ul>
Backup battery connection		YES, lead-acid 12V
Battery charging current		max. 350mA
Charging voltage		13.8V
Threshold of signaling low battery voltage		11V <sub>DC</sub>
Cut-off battery voltage level		below 9V
Dimension		PCB: 152 x 78 x 30mm PCB in plastic casing: 265 x 255 x 85mm
CALYPSO (wireless) parameters		
Radio		YES, 433.92MHZ (ENCODED TRANSMISSION WITH HOPPING CODE)
Wireless zones		9
Remote controls		max. 9



CREATING A SENSE OF SECURITY  
SINCE 1989

EBS Sp. z o.o.

59 Bronisława Czecha St.  
04-555 Warsaw, Poland

tel.: +48 22 518 84 00

fax: +48 22 518 84 99

e-mail: office@ebs.pl

website: www.ebs.pl