

1/4" Concealed-Mount Contacts

SM-206Q/BR

1 (25mm) Gap, Closed Loop, Brown

SM-206Q/W

1 (25mm) Gap, Closed Loop, White

Features:

Used for protecting sliding doors and windows where space is limited

1/4" Press-fit mount

15" (38cm) wire leads

Contact reed switch is SPST, deactivated rhodium on gold under-plating for a longer expected life

Unique glue/epoxy compound protects reed switch

For closed loop circuits

1" (25mm) Gap

Lifetime limited warranty



SM-206Q/BR Shown



Specifications:

Model number	SM-206Q/BR	SM-206Q/W
Circuit type	Closed loop	
Operation gap	1" (25mm)	
Color	Brown	White
Leads	Pre-wired 15", #22	
Material	Case	High-impact ABS plastic / epoxy compound
	Contact	Deactivated rhodium on gold under-plating
Contact rating	0.1A@100VDC (max)	
	1.0A@10VDC (max)	
	10W (max)	
Temperature	-15°~160°F (-25°~70°C)	
Switch cycles	50 Million (0.1mA@5VDC)	
Switch dimensions	1 7/32" x 1/4" (31x6.35mm)	
Magnet dimensions	1 1/4" x 1/4" (32x6.35mm)	
Magnet	Alnico 5	

Dimensions:

