



90° 弯头  
90° Elbow



45° 弯头  
45° Elbow



三通  
Tee



四通  
Cross

螺纹管件 Threaded Fittings  
GB/T 14626、ASME B16.11

公称通径 Nominal Pipe Size		90° 弯头、三通、四通 90° Elbow, Tess, Crosses			45° 弯头 45° Elbow			所有管件 All Fittings							
		中心至端面 Center to End			中心至端面 Center to End			端部外径 Outside Diameter of Band			最小壁厚 Minimum Wall Thickness			螺纹长度 Length of Thread Min	
		A			G			D			C			B	L2
DN	NPS	SCH80 2000	SCH160 3000	XXS 6000	SCH80 2000	SCH160 3000	XXS 6000	SCH80 2000	SCH160 3000	XXS 6000	SCH80 2000	SCH160 3000	XXS 6000	B	L2
6	1/8	21	21	25	17	17	19	22	22	25	3.18	3.18	6.35	6.4	6.7
8	1/4	21	25	28	17	19	22	22	25	33	3.18	3.30	6.60	8.1	10.2
10	3/8	25	28	33	19	22	25	25	33	38	3.18	3.51	6.98	9.1	10.4
15	1/2	28	33	38	22	25	28	33	38	46	3.18	4.09	8.15	10.9	13.6
20	3/4	33	38	44	25	28	33	38	46	56	3.18	4.32	8.53	12.7	13.9
25	1	38	44	51	28	33	35	46	56	62	3.68	4.98	9.93	14.7	17.3
32	1 1/4	44	51	60	33	35	40	56	62	75	3.69	5.28	10.59	17.0	18.0
40	1 1/2	51	60	64	35	43	44	62	75	84	4.01	5.56	11.07	17.8	18.4
50	2	60	64	83	43	44	52	75	84	102	4.27	7.14	12.09	19.0	19.2
65	2 1/2	76	83	95	52	52	64	92	102	121	5.61	7.65	15.29	23.6	28.9
80	3	86	95	106	64	64	79	109	121	146	5.99	8.84	16.64	25.9	30.5
100	4	106	114	114	79	79	79	146	152	152	6.35	11.18	18.67	27.7	33.0