


General Material				
No.	Name	Material	Q'ty	FLUID SYMBOL
1	VALVE BODY	SUS316	1	NONCORROSIVE GAS :NG
2	VALVE SEAT	SUS304/316	1	STEAM :S
3	DISC	SUS304/316 + MC Nylon	1	SUPER STEAM :SS
4	STEM	SUS304	1	HOT WATER :HW
5	SPRING	SUS304	1	NON CORROSIVE LIQUID :NL
6	SPRING SEAT	SUS304	2	
7	THREAD ROD	SUS304	1	
8	ADJUST NUT	SUS304	1	
9	CAP	SUS304	1	
10	PACKING	PTFE	2	
WORK PRESSURE(Kg/cm2)			40 ~ 165 K	
WORKING TEMP (°C)			-40°C ~ 120 °C	
WORKING FLUID			NG.S.SS.HW.NL	

Lift Type Dimensions					UNIT:mm			
NOMINAL					LIFT	L1	L2	H
P1	*	D	*	P2				
1"	*	10.5	*	1"	2	41.25	70.5	182.5

die erste®

DIE ERSTE INDUSTRY CO., LTD,
 TAICHUNG, TAIWAN

SHEET 1 OF 1		DRAWN BY: MICHELLE 2019/8/6	REVIEW BY:	APPROVAL:	UNIT: mm	DO NOT SCALE DRAWING	TITLE:	REV
REMARK					PROJECT: 	DWG. NO.	FVX-SMS, NPT END	2.0

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF «DIE ERSTE INDUSTRY CO., LTD.». ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF «DIE ERSTE INDUSTRY CO.,LTD.» IS PROHIBITED.