



Wt.	Ø NB	A	B	C	Ø D	E	F	G	Ø H
	15	130	14	45	95	4	14	65	115
	20	150	16	58	105	4	14	75	115
	25	160	16	68	115	4	14	85	135
	32	180	16	78	140	4	18	100	135
	40	200	18	88	150	4	18	110	150
	50	230	20	102	165	4	18	125	150
	65	290	20	122	185	4	18	145	220
	80	310	22	138	200	8	18	160	220
	100	350	24	158	220	8	18	180	295
	125	400	26	188	250	8	18	210	295
	150	480	26	212	285	8	23	240	295
	200	600	30	268	340	12	23	295	390
	250	730	32	320	405	12	26	355	390
	300	850	32	378	460	12	26	410	390

10	HAND WHEEL	CAST IRON / MALLEABLE IRON
9	GLAND	C.I. / GG 25
8	GLAND PACKING	PURE GRAFOIL
7	NUT & BOLT	ASTM A 193 GR B7 & A 194 GR 2H
6	GASKET	PURE GRAPHITE
5	SPINDLE	STAINLESS STEEL AISI 410
4	STOPPER	STAINLESS STEEL AISI 410
3	SEAT RING	CARBON STEEL WITH 13 % CHROME FACING
2	BONNET	C.I. / GG 25
1	BODY	
No.	DESCRIPTION	MATERIAL

**MATERIAL & DESCRIPTIONS**

NOTE :- ALL DIMENSIONS ARE IN mm

SPECIFICATION OF STANDARDS			TITLE :-		PROJ :-	
DESIGN	DIN 3356 / F1		PN -16 GLOBE VALVE ( FLANGE ENDS )			
FACE TO FACE	B 16.10					
FLANGED STD :-	ISO 2631		WEIGHT OF GLOBE VALVE		DRN BY	L.B.G.
TEST & INSPECTION	API 598				CHECK BY	A.R.D.
TESTS PRESSURE (Kg / Cm <sup>2</sup> )			Aprox. Wt.		APPD BY	R. E. D.
	HYDROSTATIC	AIR			SCALE	N.T.S.
BODY	25	--	Kg.		DATE	07.01.2008
SEAT & BACK SEAT	16	6				
DRG. No.	DV / GLB / PN -16 / FE / A / 01		REV. No.	0		



*Dalsons Valves*

D- 58, MIDC MIRAJ BLOCK MIRAJ  
DIST - SANGLI ( M.S. ) INDIA

NOTE :-  
1. AS CONTINUOUS IMPROVEMENT IN DESIGN PROCESS  
THE DIMENSIONS MENTIONED HERE ARE SUBJECT TO CHANGE