

DHI-LM55-F400 55" UHD LED Monitor



Features:

- \cdot 4K Ultra-HD resolution
- \cdot Suitable for continuous 24/7 operation
- · 8ms response time for no motion blur, judder or ghosting
- \cdot 1.07G colors, for a realistic and immersive visual experience
- \cdot High fidelity digital processing for a brilliant and vivid video
- \cdot 178°/178° extra-wide viewing angle for overall viewing performance
- \cdot Professional thermal design to extend equipment lifespan




Technical Specification

Model			
Model	DHI-LM55-F400		
Display			
Screen Size	55"		
Aspect Ratio	16:9		
Resolution	3840×2160 (UHD)		
Backlight	LED		
Brightness	300cd/m ²		
Contrast Ratio	1200:1		
Display Color	1.07G (8bit+FRC)		
Viewing Angle	178°(H)/178°(V)		
Response Time	8ms		
Refresh Rate	60Hz		
Signals			
Input	HDMI 2.0×1, HDMI 1.4×1, VGA×1, USB 2.0×1, Audio×1, RJ45(RS232)×1		
Output	Speaker	7W×2	
General			
Power Supply	AC100~240V (+/-10%), 50/60 Hz		

Power Consumption (Typical)	95W			
Power Consumption (Standby)	≤0.5W			
Power Type	Internal			
Net Weight	11.9kg (26.2lb)			
Gross Weight	16.1kg (35.5lb)			
Bezel Width	8.2mm (U/L/R), 20.7mm (B)			
VESA	200×200mm			
Product Dimension (W×H×D)	1230.1×786.9×268.9mm (48.4"×40.0"×10.6")			
Package Dimension (W×H×D)	1360×860×160mm (53.5"×33.9"×6.3")			
Work Environment	Temperature	0°C~40°C (32°F~104°F)		
work Environment	Humidity	20%~80%		
Accessory				
Standard	Pedestal, HDMI cable, power cable, remote control			
Optional	Hanging bracket (P/N 1.5.01.98.01656)			
Certifications				
Certifications	CE			

Light Series | DHI-LM55-F400





Rev 002.000 © 2022 Dahua. All rights reserved. Design and specifications are subject to change without notice. The images, specifications and information mentioned in the document are only for reference, and might differ from the actual product.

www.dahuasecurity.com